




Double face PVC coating - Suitable for stitch-sewing or heat-sealing



BLANCO
6931



HUESO
6920



MARFIL
6921



AVENA
6922



SILVER
6923



GRAFITO
6928



MARINO
6924




AZUL REAL
6926




NARANJA
6927




BOTELLA
6925




GRANATE
6929



NEGRO
6930



One face PVC coating - Suitable for stitch-sewing



MARFIL RAL 1013
6705



SILVER RAL 7047
6707



GRIS OSCURO RAL 7037
6704



AMARILLO RAL 1003
6708



ROJO RAL 3020
6709



GRANATE RAL 3005
6703




AZUL CLARO RAL 5005
6700



MARINO RAL 5013
6706



MUSGO RAL 6005
6711



BLANCO
6701

Cover & Cover PRO

by TUVATextil












Outdoor

Cover & Cover PRO

TUVATextil

Ctra. Pla de Sta. Maria s/n, 43817 - El Pont d'Armentera - SPAIN
Tel: +34 977 639 132 · Fax: +34 977 639 268
info@tuvatextil.com · www.tuvatextil.com

TECHNICAL FILE CARACTERISTICAS GENERALES	Cover Pro	Cover
Composition Composición	Polyester AT 550 dtex Poliester	Polyester AT 280 dtex Poliester
Coating Recubrimiento	PVC 2 faces PVC 2 caras	PVC 1 face PVC 1 cara
Width / Ancho	220 cm / 86"	210 cm / 82.6"
Weight / Peso	410 gr / m ²	300 gr / m ²
Thickness / Espesor	0.36 mm	0.27 mm
Length of rolls / Longitud de las piezas	50 ml	
Tear strength Resistencia al desgarre	Warp / Urdimbre - 13 daN	Warp / Urdimbre - 9 daN
	Weft / Trama - 10 daN	Weft / Trama - 8 daN
Temperature resistance Resistencia a la temperatura	- 30° / + 70°	
Tolerance Tolerancia	Sensitive values of tolerance of + / - 5% Valores susceptibles de tolerancia de + / - 5%	
Application / Aplicaciones		
Making / Confección		

							
WATER RESISTANT	STAIN RESISTANT	MOLD RESISTANT	UV PROTECT	UV RESISTANT	DURABLE STRONG	NO CONDUCTOR	EASY TO CLEAN



OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100



TUVATextil